



PLACE A STRIP OF 3"-wide, GREEN, PLASTIC, ELECTRONICALLY DETECTABLE TAPE 1 foot BELOW PAVEMENT SUBGRADE, ABOVE PT. OF CONNECTION

FINISHED ROAD SURFACE (SEE STANDARD DWG. NOS. 300 AND 301 SERIES AND OTHER REQUIREMENTS BY THE ENGINEERING DIVISION) CURB & GUTTER

SEE STD. CLEANOUT DETAIL (U. O. A.)

NEW 4" STREET 45' SDR 26

SEWER MAINLINE

NEW WYE PVC SDR26 (SEE NOTE 3)

MIN. 2% SLOPE (unless otherwise approved)

HDPE, PVC or ABS Sch. 40

PROPERTY OWNER SHALL BE RESPONSIBLE FOR MAINTAINING THIS PORTION

REFER TO STANDARD DWG NOS. WW100, 300 AND 301 FOR TRENCH DETAILS AND REQUIREMENTS

NOTES:

1. (U. O. A.) UNLESS OTHERWISE APPROVED
2. ALL SIDEWALK CLEAN-OUT SHALL BE RELOCATED 2' BEHIND PROPERTY LINE
3. THE PVC WYE AND MAIN SEWER SHALL BE JOINED USING MISSION ARC COUPLING OR EQUAL. SEE STANDARD DWG. NO. WW100 FOR ADDITIONAL DETAILS.

CITY OF PACIFICA DEPARTMENT OF PUBLIC WORKS WASTEWATER DIVISION	STANDARD SANITARY SEWER COLLECTION SYSTEM BUILDING SEWER LATERAL PVC SDR 26			△		SEP 2013	DWG. NO. WW201
				△			
	REV	DATE	BY:		CREATED BY: M. Aguilar		